

Line Interactive UPS

S

SPECIFICATION

Alfa
Digital

Model	RS-232	Alfa Digital-5765A
Capacity		650VA/385W
Input	Voltage	220/230/240VAC
	Voltage Range	172VAC ~288VAC (+/-25%)
	Frequency	220V 50Hz
Output	Voltage Regulation (Batt. Mode)	220/230/240VAC +/-10%
	Frequency	50Hz +/-1 Hz
	Waveform	Simulated Sinewave
	Transfer Time	< 6ms (Typical)
	Outlets: IEC-320/NEMA5-15R	4/2
Battery	Battery Type	12V/7Ah*1pc
	Recharge Time	5Hrs to 90% after complete discharge
	User's Replacement	Yes
	Battery Protection	Over discharge protection & Short circuit protection by fuse
	Advanced Battery Management	Yes
	Battery Back-up Time	20mins (Load with 1 PC)
Function	Display	LED status indicators for AC normal, Back-up,UPS cut off
	Alarm	Buzzer on for Back-up mode, Battery low
	Output Short Protection	AC fuse and Electronic circuit (Line mode); Electronic circuit (Back-up mode)
	Communication Port	Shutdown software for Windows 95/98/NT/2000/ME/XP/Vista
	Modem/Phone Protection	RJ-11
	Lightning/Surge Protection	240joules
	AVR (Auto. Voltage Regulation)	Boost/Buck
	DC Start Function i	Yes
	Auto. Restart UPS	Yes
	Over/Under Voltage Protection	Yes
Environment	Safety Standard	CE (EN 50091-1, EN 62040-1-1)
	EMC Standard	FCC Part 15 Class B,CE (EN 50091-2, EN 55011, EN 61000-3-2, EN 61000-3-3)
	Operating Temperature	0 ~ 40°C
	Relative Humidity	0 ~ 95 % non-condensing
	Audible Noise	< 40dB at 1M
Physical	Dimension (D*W*H)	290*95*170mm
	Net Weight	6.5 Kgs
Design, Manufacture, Services		ISO 9001-2000
Warranty		1 year