

		INVISIMO-1000	INVISIMO-1500	INVISIMO-2000	INVISIMO-3200
Model		INVISIMO-1000	INVISIMO-1500	INVISIMO-2000	INVISIMO-3200
Capacity		1000VA/600W	1500VA/900W	2000VA/1200W	3200VA/2000W
Input	AC Voltage	110/115/120VAC or 220/230/240VAC, 1 Phase+Neutral			
	Voltage Tolerance (AC)	90VAC~135VAC or 187VAC~264VAC +/-4%			
	DC Voltage	12VDC		24VDC	
	Voltage Tolerance (DC)	10VDC ~ 14VDC		20VDC-28VDC	
	Frequency	47Hz~50Hz or 57Hz~63Hz			
Output	Voltage	110/115/120VAC or 220/230/240VAC			
	Voltage Tolerance (Batt. Mode)	+/- 7%			
	Frequency	50Hz			
	Frequency Tolerance	+/- 1Hz in Battery Mode			
	Transfer Time	< 10ms (Typical)			
	Voltage Waveform	Simulated Sinewave			
Battery	Type	Maintenance free dry type (suggested)			
	Capacity	Up to 1000AH			
	Battery Low Level	10.8V+/-0.2V		21V+/-0.5V	
	Battery Cut off Level	10V+/-0.2V		20V+/-0.5V	
	Battery House	External: Rack or Cabinet (Optional)			
Charger	Battery Charge Voltage	13.6VDC+/-0.2VDC		27.5VDC+/-0.3VDC	
	Charge Capacity	30A max. (Adjustable)			
	Over Charge Protection	14.5VDC+/-0.5VDC		29VDC+/-0.5VDC	
Display & Control Panel	Control Panel		Power On/Off & UPS Test button. Battery charge current adjustment		
	Indicators	Line Mode	AC normal LCD lighting		
		Battery Mode	Back-Up LCD lighting		
		Overload	O-Load LCD lighting		
		Over Temp	O-Temp LCD lighting		
		UPS off	Cut off LCD lighting		
		Load Level	5-step LCD lighting		
Battery Level	5-step LCD lighting				
Protection	Full Protection	Overload. Short circuit, Over charge, Over temperature, Input & Output fuse			
Environment	Audible Noise	< 45dB at 1M			
	Operating Temperature	0 ~ 40°C			
	Storage Temperature	-20°C ~ 70°C			
	Relative Humidity	Maximum 0 ~ 90% (non-condensing)			
	Type of Cooling	Forced with fan			
	Installation Height	< 3000 meters, elevation			
Physical	Dimension(D*W*H)	420*218*160mm			
	Weight, w/o Battery	11Kgs	14Kgs	16Kgs	20Kgs
Design, Manufacturer, Services		ISO 9001-2000			
Warranty		1 year			